

品名 (定格電圧)	公称 断面積 mm ²	導体		絶縁体 厚さ mm	編組 厚さ mm	仕上 外径 mm	導体抵抗 (23℃・標準) Ω/km	絶縁抵抗 (20℃・最小) MΩ・km	試験電圧 (AC1分) V	1条の 最大長さ m	概算 質量 kg/km
		構成 本/mm	導体外径 mm								
LKGB (600V) <PSE>	0.75	30/0.18	1.1	1.1	0.5	4.4	25.8	100	1500	100	30
	1.25	50/0.18	1.5	1.1	0.5	4.7	15.5	100	1500	100	40
	2	37/0.26	1.8	1.1	0.5	5	9.91	100	1500	100	50
	3.5	45/0.32	2.4	1.1	0.5	5.7	5.38	100	1500	100	70
	5.5	35/0.45	3.1	1.1	0.5	6.3	3.5	90	1500	100	90
	8	50/0.45	3.7	1.1	0.5	6.9	2.45	80	1500	100	120
	14	88/0.45	4.9	1.1	0.6	8.3	1.39	60	2000	100	200
	22	7/20/0.45	7	1.4	0.6	11	0.892	70	2000	100	310
	38	7/34/0.45	9.1	1.4	0.6	13.1	0.525	50	2500	100	520
	60	19/20/0.45	11.6	1.8	0.6	16.2	0.329	50	2500	100	750
	100	19/24/0.45	15.2	2.3	0.7	21.2	0.193	50	2500	100	1270
150	27/34/0.45	18.7	2.3	0.7	24.7	0.136	40	3000	100	1810	

	200	37/34/0.45	21.2	2.9	0.7	28.4	0.0993	40	3000	100	2370
--	-----	------------	------	-----	-----	------	--------	----	------	-----	------